# TANGO



#### ORDERING INFORMATION **PART NUMBER** DESCRIPTION INSTRUMENT CONFIGURATIONS TX1-1 Tango TX1, CO TX1-2 Tango TX1, H<sub>2</sub>S TX1-4 Tango TX1, NO<sub>2</sub> TX1-5 Tango TX1, SO<sub>2</sub> **ACCESSORIES** 18109201 iNet DS docking station for Tango\* 17154367 Replacement battery 18109171 Soft nylon case, Black 18109239 Soft nylon case, Orange 18109218 Dust barrier kit, 5 pack 18109230 Water barrier kit, 5 pack 18109238 CalCup and tubing kit 17120908 Belt clip 17154915-0 AlarmAmp™, Black 17154915-1 AlarmAmp™, Safety Orange 17154916 Black nameplate 17154917 Green nameplate 17154918 Yellow nameplate 17154919 Blue nameplate 17154920 White nameplate

# **SINGLE GAS MONITOR**

# **SPECIFICATIONS**

## **INSTRUMENT WARRANTY:**

Three year warranty which does not include battery, sensors and filters. CO and  $H_2S$  sensors are warranted for 3 years from the initial purchase date. All other sensors are warranted for 2 years from the initial purchase date.

## DISPLAY:

Segment liquid crystal display (LCD)

## **KEYPAD:**

Two buttons

#### CASE MATERIALS:

Case top: Polycarbonate with a protective rubber overmold Case bottom: Conductive polycarbonate

#### ALARMS:

Three strobe-emitting visual alarm LEDs (two red; one blue); 100 decibel (dB) audible alarm at a distance of 10 cm (3.94"); Vibration alarm

#### **DIMENSIONS:**

99 x 51 x 35 mm (3.9" x 2.0" x 1.4")

## **WEIGHT:**

126.0 g (4.4 oz.)

## **OPERATING TEMPERATURE RANGE:**

-20°C to +50°C (-4°F to +122°F)

## **OPERATING HUMIDITY RANGE:**

15%-95% Non-condensing (continuous)

#### **INGRESS PROTECTION:**

IP66; IP67

## **SENSORS:**

CO, H<sub>2</sub>S, NO<sub>2</sub>, SO<sub>2</sub> - Electrochemical sensor technology

# **SENSOR MEASURING RANGES:**

Carbon Monoxide (CO):
Hydrogen Sulfide (H<sub>2</sub>S):
Nitrogen Dioxide (NO<sub>2</sub>):

Sulfur Dioxide (SO<sub>2</sub>):

0 to 1,000 ppm in 1 ppm increments
0.0 to 200.0 ppm in 0.1 ppm increments
0.0 to 150.0 ppm in 0.1 ppm increments
0.0 to 150.0 ppm in 0.1 ppm increments

## **BATTERY:**

3.6 V Primary lithium-thionyl chloride (Li-SOCI2), 1.5AH, 2/3AA, replaceable, nonrechargeable; always on; 3 year run time depending on operating conditions

# DATALOGGING:

3 months at 10-second intervals

# **EVENTLOGGING:**

60 alarm events

## **CERTIFICATIONS:**

ATEX Ex ia I Ma

Ex ia IIC T4 Ga

Equipment Group and Category: I M1 and II 1G

China Ex Ex ia IIC T4 Ga

CSA Ex ia IIC; Class I, Groups A B C D; T4
IECEx Ex ia I Ma

Ex ia IIC T4 Ga

UL (C-US) Class I, Groups A, B, C, and D; Class II, Groups E, F, and G; T4; Exia

Class I, Zone 0, AEx ia IIC T4

PENDING:

MSHA Permissible Gas Monitor

INMETRO Ex ia IIC T4

These specifications are based on performance averages and may vary by instrument.

\*The Tango is warranted to be free from defects in material and workmanship under normal and proper use and service for 3 years from the initial purchase date.

# Distributed by:



# Contact Details:

12 Johnstone Drive Rutherglen Glasgow G73 2PT Scotland, UK

www.amsequipment.com / sales@amsequipment.com / 0141 587 8296

<sup>\*</sup>Access to data from the iNet DS docking station requires a subscription to iNet or iNet InSite.